

HUNTING CONTENTS

VAP SS	1
VAP TKO	2
RIP TKO	
VF TKO	
VAP	5
RIP XV	6
RIP	
VForce	
VForce Jr	9
X Bolt	10
VooDoo SS	
VooDoo	12
Accessories	13
Fitting Charts	
Spine Charts	17
Safety Warning	18

DIGITALLY SPINE ALIGNED FOR
INCREASED ACCURACY AND CONSISTENCY

MAXX KE TECHNOLOGY

ADVANCED 3K CARBON WEAVE FOR LESS TORQUE, FASTER RECOVERY OF FLIGHT, AND SPINE CONSISTENCY




EACH DOZEN WEIGHT MATCHED TO +-0.5 GRAINS FOR PRECISE SHOT CONSISTENCY AND TIGHTER GROUPING

HAND FLETCHED FOR
OPTIMUM VANE ADHESION AND ALIGNMENT

ADVANCED NANO CERAMIC

ARROW COATING IMPROVES PENETRATION



speed and penetration with less wind deflection



A bone-crushing carbon fiber/stainless steel hunting arrow

JAR<u>CHERY •</u>

- > FASTER ARROW RECOVERY ON SHOT
- > UNSURPASSED PENETRATION
- > HIGH FOC & MOMENTUM
- > LESS AFFECTED BY WIND
- > ADVANCED 90° 3K CARBON WEAVE




The VAP-SS™ has proven itself to be the pinnacle of hunting arrow technology; a bone-crushing, micro-diameter shaft with stainless steel layers infused into a 90° carbon fiber weave, the VAP-SS™ is lighter and faster than its predecessor, the Xtorsion™. With higher FOC and the same sledge-hammering momentum, this shaft will punch through anything in its path and is sure to stay straight shot after shot.





PERFORMANCE GUIDE



SHOK™ TL BROADHEAD ADAPTOR 50GR - 7075 Aluminum Alloy 75 or 95GR Stainless Steel upgrade for extreme FOC

Improved impact protection sleeve strengthens arrow tip from fracturing - increasing impact resilience and durability. Patent pending taper lock machining improves strength and concentricity.

Shok* TL adaptor accepts standard 5/16" broadheads with 8-32 thread allowing you to continue using your favorite broadhead for trusted performance.

STRAIGHTNESS TOLERANCES + .001"/+0.5gr

SPECIFICATIONS CHART

SPINE	SHAFT WEIGHT GPI	SHAFT LENGTH INCHES	SHAFT ID	SHAFT OD	SHAFT STRAIGHTNESS
250	10.8	31.0	0.166	0.247	
300	9.9	31.0	0.166	0.241	± 0.001 Elite
350	8.8	31.0	0.166	0.234	± 0.003 Gamer ± 0.006 Sport
400	8.6	31.0	0.166	0.232	

ACCESSORIES

SHOK TM TL ALUMINUM INSERT 50GR SHOK TM TL SS/AL INSERT 75GR SHOK TM TL SS/AL INSERT 75GR		
50GR SHOK™TL SS/AL INSERT 75GR	INCLUDED	OPTIONAL
	50GR	

PRO SHOP ONLY

Patent pending



+ .006"/+0.5gr

VICTORY ARCHERY (1)





APTKO

The ultimate hunting arrow

- > FASTER ARROW RECOVERY ON SHOT
- > EXCELLENT PENETRATION & MOMENTUM

PAR<u>CHERY •</u>

- > EXTREME FOC
- > LESS AFFECTED BY WIND
- > ADVANCED 3K CARBON WEAVE

INSIDE DIAMETER



MICRO DIAMETER ARROW - 100% carbon fiber construction 0.166 diameter for maximum speed and penetration with less wind deflection



The ultimate long-range hunting arrow with our highest recorded kinetic energy at 100 yards! By reducing the torsional deflection associated with the twisting of the arrow shaft at launch, the arrow shaft stabilizes much faster while increasing the retained kinetic energy down range. This makes the VAP TKO™ the most accurate hunting arrow in the Victory arsenal in addition to the deepest penetrating arrow shot from a vertical bow.





PERFORMANCE GUIDE



SHOK™ TL BROADHEAD ADAPTOR 50GR - 7075 Aluminum Alloy 75 or 95GR Stainless Steel upgrade for extreme FOC



Improved impact protection sleeve strengthens arrow tip from fracturing - increasing impact resilience and durability. Patent pending taper lock machining improves strength and concentricity.

Shok* TL adaptor accepts standard 5/16" broadheads with 8-32 thread allowing you to continue using your favorite broadhead for trusted performance.

STRAIGHTNESS TOLERANCES

+ .001"/+0.5gr

SPECIFICATIONS CHART

SPINE	SHAFT WEIGHT GPI	SHAFT LENGTH INCHES	SHAFT	SHAFT OD	SHAFT STRAIGHTNESS
235	11.1	31.0	0.166	0.252	
300	9.5	31.0	0.166	0.242	+ 0.001 Elite
350	8.7	31.0	0.166	0.236	+ 0.003 Gamer + 0.006 Sport
400	7.9	31.0	0.166	0.231	

ACCESSORIES



PRO SHOP ONLY

STRAIGHTNESS TOLERANCES

+ .003"/+0.5gr

STRAIGHTNESS TOLERANCES











0.204"



The perfect combination of speed, power, and durability

PAR<u>CHERY :</u>

- > FASTER ARROW RECOVERY ON SHOT
- > EXCELLENT PENETRATION
- > INCREASED FOC
- > LESS AFFECTED BY WIND
- > ADVANCED 3K CARBON WEAVE

- 100% carbon fiber construction .204 diameter for maximum speed and penetration with less wind deflection

SMALL DIAMETER ARROW








Hunters looking for the perfect combination of speed, power, and durability need look no further than the RIP TKO™. This .204 diameter shaft is smaller than standard hunting arrows which reduces wind drift and increases penetration while maintaining extreme durability. MaxxKe™ Technology also increases kinetic energy during impact, helps the arrow to recover guicker in flight, and ensures your arrow hits hard every time you let it RIP™.







PERFORMANCE GUIDE



SPECIFICATIONS CHART

SPINE	SHAFT WEIGHT GPI	SHAFT LENGTH INCHES	SHAFT	SHAFT OD	SHAFT STRAIGHTNESS
250	8.9	31.0	0.204	0.266	
300	8.8	31.0	0.204	0.266	+ 0.001 Elite
350	8.7	31.0	0.204	0.265	+ 0.003 Gamer + 0.006 Sport
400	9.0	31.0	0.204	0.266	

SHOK™ TL204 BROADHEAD ADAPTOR

50GR - 7075 Aluminum Alloy 75GR Stainless Steel upgrade for extreme FOC



Improved impact protection sleeve strengthens arrow tip from fracturing - increasing impact resilience and durability. Patent pending taper lock machining improves strength and concentricity.

Shok™ TL adaptor accepts standard 5/16" broadheads with 8-32 thread allowing you to continue using your favorite broadhead for trusted performance.

STRAIGHTNESS TOLERANCES + .003"/+0.5gr

STRAIGHTNESS TOLERANCES

± .001"/±0.5gr

ACCESSORIES



PRO SHOP ONLY

STRAIGHTNESS TOLERANCES + .006"/+0.5gr







INSIDE DIAMETER



0.245"

Redefining the standard-diameter high quality hunting arrow

O ARCHERY

- > HIGHEST PERFORMING STANDARD DIAMETER ARROW
- > LOW TOROUE TECHNOLOGY
- > FASTER ARROW RECOVERY ON SHOT
- > ADVANCED 3K CARBON WEAVE

ARROW - .245 standard diameter 100% carbon fiber construction for increased

durability and consistency.




The VF TKO™ is the ultimate standard diameter hunting arrow. The 100% all carbon shaft incorporates MaxxKe™ Technology increasing kinetic energy during impact and allowing for faster arrow recovery in flight. These arrows are the fastest recovering, most accurate standard diameter arrow offered in the industry.



MATCHED WEIGHT



PERFORMANCE GUIDE



STRAIGHTNESS TOLERANCES

+ .001"/+0.5gr

SPECIFICATIONS CHART

SPINE	SHAFT WEIGHT GPI	SHAFT LENGTH INCHES	SHAFT ID	SHAFT OD	SHAFT STRAIGHTNESS
250	10.1	31.0	0.245	0.306	
300	9.5	31.0	0.245	0.302	+ 0.001 Elite
350	8.7	31.0	0.245	0.297	+ 0.003 Gamer + 0.006 Sport
400	8.1	31.0	0.245	0.295	

ACCESSORIES



PRO SHOP ONLY

STRAIGHTNESS TOLERANCES

+ .003"/+0.5gr

STRAIGHTNESS TOLERANCES + .006"/+0.5gr

VICTORY ARCHERY (4)





.166

The VAP™ Hunting arrow has redefined industry standards for precision, penetration, and kinetic energy. These .166" micro-diameter arrows are far less affected by cross-winds at longer distances and incorporate extreme front of center technology to pack a serious punch.





> EXTREME FOC

> 100% HIGH MODULUS CARBON FIBER



	· -				
SPINE	SHAFT WEIGHT GPI	SHAFT LENGTH INCHES	SHAFT ID	SHAFT OD	SHAFT STRAIGHTNESS
250	9.8	31.0	0.166	0.244	
300	8.7	31.0	0.166	0.237	
350	7.8	31.0	0.166	0.232	± 0.001 Elite
400	7.2	31.0	0.166	0.227	± 0.003 Gamer ± 0.006 Sport
450	6.6	31.0	0.166	0.223	± 0.000 Sport
500	6.1	31.0	0.166	0.218	

ACCESSORIES



PERFORMANCE GUIDE



SHOK™ TL BROADHEAD ADAPTOR 50GR - 7075 Aluminum Alloy



Improved impact protection sleeve strengthens arrow tip from fracturing - increasing impact resilience and durability. Patent pending taper lock machining improves strength and concentricity.

Shok™ TL adaptor accepts standard 5/16" broadheads with 8-32 thread allowing you to continue using your favorite broadhead for trusted performance.

STRAIGHTNESS TOLERANCES

+ .001"/+0.5gr

STRAIGHTNESS TOLERANCES

± .003"/±0.5gr

STRAIGHTNESS TOLERANCES





The lightest, fastest hunting arrow in our arsenal

- > MINIMAL PIN GAP WHICH ALLOWS FOR SINGLE PIN SHOTS UP TO 40 YARDS
- > INCREASED SPEED FOR INCREASED KINETIC ENERGY
- > EXTREME VELOCITY, FLAT TRAJECTORY
- > SMALL DIAMETER SHAFT
- > EXTREME FOC

INSIDE DIAMETER



0.204"

SMALL DIAMETER ARROW - 100% carbon fiber construction .204 diameter for maximum speed and penetration with less wind deflection



The RIP XV™ was designed and extensively tested for two qualities – speed and long-range accuracy. Our carbon engineers synthesized different high-modulus carbon formulas to develop this sub 6 GPI ultra-light and super-deadly arrow. The .204 small diameter shaft leaves less surface area for wind deflection and its lightweight construction delivers extremely flat trajectory over long distances. Coupled with our SHOK™ insert for better penetration and high FOC the RIP XV™ is the perfect extreme velocity hunting arrow.



MATCHED WEIGHT




SPECIFICATIONS CHART

SPINE	SHAFT WEIGHT GPI	SHAFT LENGTH INCHES	SHAFT ID	SHAFT OD	SHAFT STRAIGHTNESS
250	8.0	31.0	0.204	0.260	
300	7.1	31.0	0.204	0.255	+ 0.001 Elite
350	6.4	31.0	0.204	0.251	+ 0.003 Gamer
400	5.9	31.0	0.204	0.247	+ 0.006 Sport
500	5.1	31.0	0.204	0.242	

ACCESSORIES



PERFORMANCE GUIDE



SHOK™ BROADHEAD ADAPTOR

7075 Aluminum Alloy Hard Anodized

Shok™ Adaptor accepts 8/32" broadheads allowing you to continue using your favorite broadhead for trusted performance.



Exclusive impact protection sleeve protects the tip of the arrow from fracturing - increases impact strength and durability.

> STRAIGHTNESS TOLERANCES + .001"/+0.5gr

STRAIGHTNESS TOLERANCES

+ .003"/+0.5gr

STRAIGHTNESS TOLERANCES



The most versatile arrow in our line-up for any game

- > EXCELLENT PENETRATION
- > EXTREMELY DURABLE
- > EXCELLENT PENETRATION
- > LESS AFFECTED BY WIND
- > 100% HIGH PERFORMANCE CARBON FIBER

INSIDE DIAMETER



0.204"

SMALL DIAMETER ARROW - 100% carbon fiber construction .204 diameter for maximum speed and penetration with less wind deflection







Looking for an arrow with the speed and accuracy of a small-diameter shaft but the durability and kinetic energy of a larger arrow? The RIP™ .204 small-diameter shaft reduces wind drift and the SHOK™ insert improves FOC balance while increasing penetration. This is one of the hardest hitting arrows in our arsenal to give you the confidence you need to let it RIP™.










SPECIFICATIONS CHART

SPINE	SHAFT WEIGHT GPI	SHAFT LENGTH INCHES	SHAFT ID	SHAFT OD	SHAFT STRAIGHTNESS
250	9.3	31.0	0.245	0.268	
300	8.8	31.0	0.204	0.265	+ 0.001 Elite
350	8.2	31.0	0.204	0.262	+ 0.003 Gamer
400	7.5	31.0	0.204	0.258	+ 0.006 Sport
500	7.0	31.0	0.204	0.255	

ACCESSORIES



PERFORMANCE GUIDE



SHOK™ BROADHEAD ADAPTOR

60GR Stainless Steel

Shok™ Adaptor accepts 8/32" broadheads allowing you to continue using your favorite broadhead for trusted performance.



Exclusive impact protection sleeve protects the tip of the arrow from fracturing - increases impact strength and durability.



± .001"/±0.5gr

STRAIGHTNESS TOLERANCES

± .003"/±0.5gr

STRAIGHTNESS TOLERANCES



Defining the standard-diameter high quality hunting arrow

- > SUPERIOR STRAIGHTNESS
- > EXTREMELY DURABLE
- > UNIFORM CONCENTRICITY
- > 100% CARBON FIBER CONSTRUCTION

INSIDE DIAMETER



0.245"

ARROW - .245 standard diameter 100% carbon fiber construction for increased durability and consistency.




The VForce™ arrow has defined the industry standard for high quality hunting arrows since day one. Highly advanced carbon engineering helped to craft this 100% all carbon shaft with incredible consistency and durability. If you want one of the toughest, most dependable hunting shafts on the market, then the VForce™ is for you.







PERFORMANCE GUIDE DIAMETER -(3)



SPECIFICATIONS CHART

SPINE	SHAFT WEIGHT GPI	SHAFT LENGTH INCHES	SHAFT ID	SHAFT OD	SHAFT STRAIGHTNESS
250	10.8	31.0	0.245	0.309	
300	9.7	31.0	0.245	0.304	
350	8.7	31.0	0.245	0.298	+ 0.001 Elite
400	8.2	31.0	0.245	0.295	+ 0.003 Gamer + 0.006 Sport
500	6.9	31.0	0.245	0.287	+ 0.000 Sport
600	6.6	31.0	0.245	0.287	

ACCESSORIES



STRAIGHTNESS TOLERANCES + .001"/+0.5gr

STRAIGHTNESS TOLERANCES + .003"/+0.5gr

> STRAIGHTNESS TOLERANCES + .006"/+0.5gr

VICTORY ARCHERY (8)



High performance youth arrow

- > EXTREMELY DURABLE
- > UNIFORM CONCENTRICALLY
- > 100% CARBON FIBER CONSTRUCTION

INSIDE DIAMETER



0.245"


STANDARD DIAMETER ARROW - .245 standard diameter 100% carbon fiber construction for increased durability and consistency.





The VForce JR is offered in a .245 standard diameter and available in one of the most popular youth spines. For those junior hunters that want to take their skills to the next level and shoot their first game, the VForce JR is the perfect choice. These arrows are 100% all carbon and are custom hand fletched, for precision hunting.

PERFORMANCE GUIDE



SPECIFICATIONS CHART

SPINE	SHAFT WEIGHT GPI	SHAFT LENGTH INCHES	SHAFT ID	SHAFT OD	SHAFT STRAIGHTNESS
600	6.6	31.0	0.245	0.287	+ 0.001 Elite + 0.003 Gamer + 0.006 Sport

ACCESSORIES

INCLUDED	OPTIONAL
THE RESERVE	
BLAZER NOCK 9GR	VFORCE RPS INSERT 22GR
VF INSERT 11GR	VFORCE SS INSERT 33GR
	LIGHTED SWITCH NOCK





Standard diameter bolt

- > 100% CARBON FIBER
- > MAXIMUM POWER
- > ICE COATING
- > EFOC (EXTREME FORWARD OF CENTER)
- > 100% CUSTOM HAND FLETCHED

INSIDE DIAMETER



0.300"


STANDARD BOLT – 100% carbon fiber construction 0.300 Diameter able to withstand the power of the latest crossbows.

The XBolt Crossbow bolts can withstand the power of the latest crossbows, fly true and have the knock-down power needed to get the job done. The XBolt Crossbow bolts are optimized with the EFOC (Extreme Forward of Center) design to help stabilize the arrow in flight. The XBolt includes both flat and half-moon nocks and a specially-designed brass insert. Victory's Spine Alignment process increases the accuracy and they come hand-fletched in Bohning XVanes or Fusion X-II vanes.

Weetory







PERFORMANCE GUIDE



SPECIFICATIONS CHART

SHAFT LENGTH INCHES	TOTAL WEIGHT GRAINS	INSERT WEIGHT GRAINS	SHAFT ID	SHAFT OD	SHAFT STRAIGHT- NESS
20.0	325	110	0.300	0.344	+ 0.001 Elite
22.0	325	92	0.300	0.344	+ 0.003 Gamer + 0.006 Sport

ACCESSORIES

INCLUDED	OPTIONAL
	-
BRASS INSERT 92 - 110GR	FLAT NOCK 9GR
HALF MOON NOCK 11GR	HALF MOON LIGHTED NOCK

STRAIGHTNESS TOLERANCES

± .001"/±0.5gr

STRAIGHTNESS TOLERANCES + .003"/+0.5gr

> Sport STRAIGHTNESS TOLERANCES

± .006"/±0.5gr





The world's only advanced hybrid carbon stainless steel crossbow bolt

WARNING: 2 TARGETS NEED TO STOP THIS ARROW

- > EXTREME PENETRATION
- > EXTREME SPEED
- > EXTREME DURABILITY

INSIDE DIAMETER



1 0.166"

VooDoo SS Bolt - .166 micro-diameter shaft penetrates deeper & cuts through the wind like no other holt can







The Voodoo-SS builds on a decade of success to create the world's best penetrating bolt with stainless steel mesh woven into the carbon for extreme durability. With the improved SHOK™TL outsert and reconfigured vane offset, the Voodoo-SS is the most accurate, hard hitting and durable bolt we have ever made.




MATCHED WEIGHT



AR<u>CHERY •</u>

PERFORMANCE GUIDE



EXTRA CLEARANCE ABOVE THE RAIL

Allows for a helical vane configuration yielding a faster spin rate off the rail

UNBELIEVABLE PENETRATION Ultra small diameter for incredable

speed and accuracy with unmatched

ONLY 2 RAIL CONTACT POINTS NOCK AND RAIL RYDER

95% less arrow contact with the rail


SHOK™ TL BROADHEAD ADAPTOR SOGR - 7075 ALUMINUM ALLOY

STRAIGHTNESS TOLERANCES + .003"/+0.5gr

SPECIFICATIONS CHART

SHAFT LENGTH INCHES	TOTAL WEIGHT GRAINS	INSERT WEIGHT GRAINS	SHAFT ID	SHAFT OD	SHAFT STRAIGHT- NESS
20.0	315	50	0.166	0.241	<u>+</u> 0.003

2 TARGETS NEEDED TO STOP THIS BOLT - EXTREME PENETRATION - EXTREME SPEED - EXTREME DURABILITY



SELECT ACCESSORIES

Check out victoryarchery.com for ordering information.



VICTORY BOND

Victory Bond is a fast setting, lowviscosity cyanoacrylate based adhesive. Vanes, feathers or nocks, carbon, wood or aluminum, it makes no difference, Victory Bond has you covered. This high quality adhesive gives you the peace of mind that what you glue will stay glued. Use sparingly for the strongest bond, and this bottle will fletch hundreds of arrows



BLACK FUSION

Black Fusion by Victory Archery is the industry's toughest insert glue. Rubberized particles blended into the adhesive allow the bond to maintain elasticity while providing superior hold. This unique blend ensures the bond between arrow and component never crystalizes or fractures, allowing for repeated high impact revolutions without the fear of failure.









quarter zip, relaxed fit. Available in S-XXXL

SELECT ACCESSORIES (CONTINUED)



"VICTORY PULSE" T-SHIRTS

A super comfortable cotton polyester blend for the range, scouting and everywhere in between. Available in S-XXXL

"VICTORY ARROW" T-SHIRTS

A super comfortable cotton polyester blend for the range, scouting and everywhere in between.

Available in S-XXXL



"VICTORY BOW" HOODIES

A super comfortable cotton polyester blend for the range, scouting and everywhere in between.

Available in S-XXXL





"VICTORY FLAG" HOODIES

A super comfortable cotton polyester blend for the range, scouting and everywhere in between.

Available in S-XXXL

FITTING CHARTS

VICTORY VAP SHOK .166/MICRO DIAMETER INSERT APPLICATION CHART								
INSERT	PART #	GR WEIGHT	VAP	VAP TKO	VAP-SS			
	ACVAPI229GN	34 GR ALUM	400, 500, 600					
	ACVAPI234GY	CVAPI234GY 34 GR ALUM		400	400			
	ACVAPI241BL	34 GR ALUM	250, 300	300, 350	350			

INSERT	PART #	GR WEIGHT	RIP	RIPXV	RIP TKO
	ACRIPI260GN	21 GR ALUM	400 500	300, 350,	
	ACRIPI260SS	60 GR SS	400, 500	400, 500	
	ACRIPI264GY	21 GR ALUM	252	050	
	ACRIPI264SS	60 GR SS	350	250	
	ACRIPI267BL	21 GR ALUM	200		250, 300
	ACRIPI267SS	60 GR SS	300		350, 40

VICTORY SHOK CARBON TRAD INSERT APPLICATION CHART									
INSERT	PART #	GR WEIGHT	Carbon Trad						
	ACRIPI279SS	80 GR SS	650, 550						
	ACRIPI283SS	80 GR SS	350, 450						

TORY SHOK TAPER I	LOCK (TL204) INSER	T APPLICATION	CHART			
INSERT	PART #	GR WEIGHT	XTORSION	RIPTKO	RIP	RIPXV
	ACISHOKRS	50 GR ALUM			400, 500 300, 350	300, 350
	ACISHOKRSS	75 GR ALUM/SS				400, 50
	ACISHOKRM	50 GR ALUM	400	250, 300,		250
	ACISHOKRMS	75 GR ALUM/SS	400	350, 400		
	ACISHOKRL	50 GR ALUM	200 250			
	ACISHOKRLS	75 GR ALUM/SS	300, 350			
20	ACISHOKRXL	50 GR ALUM	050			
	ACISHOKRXLS	75 GR ALUM/SS	250			

FITTING CHARTS (CONTINUED)

INSERT	PART #	GR WEIGHT	VAP	VAP TKO	VAP-SS
	ACISHOKVS	50 GR ALUM			
	ACISHOKVSS	75 GR ALUM/SS	400, 450, 500		
	ACISHOKVS95	95 GR SS			
	ACISHOKVM	50 GR ALUM			
	ACISHOKVMS	75 GR ALUM/SS	350	400	400
	ACISHOKVM95	95 GR SS			
	ACISHOKVL	50 GR ALUM		350	350
	ACISHOKVLS	75 GR ALUM/SS	300		
	ACISHOKVL95	95 GR SS			
	ACISHOKVXL	50 GR ALUM		300	
	ACISHOKVXLS	75 GR ALUM/SS	250		300
	ACISHOKVXL95	95 GR SS			
	ACISHOKVXXL	50 GR ALUM			
The state of the s	ACISHOKVXXLS	75 GR ALUM/SS			250
	ACISHOKVXXL95	95 GR SS			

RI BACK WEIGHT	APPLICATION CHART	
INSERT	PART #	GR WEIGHT
mat .	ACBW204-10-12	.204 Dia 10gr backweight 12pk
m	ACBW204-20-12	.204 Dia 20gr backweight 12pk
m ()	ACBW204-50-12	.204 Dia 50gr backweight 12pk
MILE TO SERVICE STATE OF THE PARTY OF THE PA	ACBW245-10-12	.245 Dia 10gr backweight 12pk
Mr. Carl	ACBW245-20-12	.245 Dia 20gr backweight 12pk
mr (masses)	ACBW245-50-12	.245 Dia 50gr backweight 12pk
	ACAW	Backweight wrench



3		L			
1	8				
		1	Second.	Microson	
1			1	AU.	
E				A	A
r	ı	F		1	1
1	1				
	ľ		۱		
5					
5		7	A		
	1				

IMPORTANT NOTES						
Below 300 FPS	Deduct 5 lbs Draw Weight					
300-330	Baseline Draw Weight					
331-351	Add 5 lbs Draw Weight					
Above 351 FPS	Add 10 lbs Draw Weight					

If draw length and poundage fall on the edge of a spine with a 100 or 125 grain point, choose the stiffer spine

THIS CHART IS FOR GENERAL REFERENCE ONLY, FOR DETAILED SPINE INFO VISIT www.victoryarchery.com/arrow-guide/

	VF/RIP XV SPINE CHART								
Compound				P	rrow Lengt	h			
Bow Rating 300-340 FPS	23"	24"	25"	26"	27"	28"	29"	30"	31"
37-41					500	500	500	500	500
42-46				500	500	500	500	500	400
47-51		500	500	500	500	400	400	400	400
52-56	500	500	500	400	400	400	400	400	350
57-61	500	500	400	400	400	400	400	350	350
62-66	400	400	400	400	350	350	350	350	300
67-72	400	400	400	350	350	350	350	300	300
73-78	400	400	350	350	300	300	300	300	300
79-84	350	350	350	300	300	300	300	250	250
85-90	350	350	300	300	300	250	250	250	250
90-95	300	300	300	250	250	250	250	250	
95-100	300	300	250	250	250	250			

Spine Calculation based on Standard 21/22 Grain Insert

				VAP TKO/VAP SS/RIP/RIP TKO SPINE CHART										
Arrow Length														
23"	24"	25"	26"	27"	28"	29"	30"	31"						
				500	500	500	500	500						
			500	500	500	500	500	400						
	500	500	500	500	400	400	400	400						
500	500	500	400	400	400	400	400	350						
500	500	400	400	400	400	400	350	350						
400	400	400	400	350	350	350	350	300						
400	400	400	350	350	350	350	300	300						
400	400	350	350	300	300	300	300	300						
350	350	350	300	300	300	300	250	250						
350	350	300	300	300	250	250	250	250						
300	300	300	250	250	250	250	250							
300	300	250	250	250	250									
	500 500 400 400 400 350 350 300 300	500 500 500 500 400 400 400 400	500 500 500 500 500 500 500 400 400 400 400 400 400 400 400 400 350 350 350 350 350 350 300 300 300 300 300 300 250	23" 24" 25" 26" 500 500 500 500 500 500 500 400 500 500 400 400 400 400 400 400 400 400 400 350 400 400 350 350 350 350 350 300 300 300 300 250 300 300 250 250	23" 24" 25" 26" 27" 500 500 500 500 500 500 500 500 500 500 500 400 400 400 400 400 400 400 400 350 400 400 400 350 350 350 350 350 300 300 350 350 300 300 300 300 300 300 250 250	23" 24" 25" 26" 27" 28" 500 500 500 500 500 500 500 500 500 400 500 500 500 400 400 400 500 500 400 400 400 400 400 400 400 400 400 350 350 350 350 400 400 400 350 350 350 300 300 300 350 350 350 300 300 300 250 250 250 300 300 300 250 250 250 250	23" 24" 25" 26" 27" 28" 29" 500 500 500 500 500 500 500 500 500 500 500 400 400 400 400 500 500 500 400 400 400 400 400 400 400 400 400 400 400 400 400 400 400 400 350 350 350 350 350 350 350 350 350 350 300 300 300 300 300 300 300 300 300 300 300 300 300 300 300 300 300 300 250	23" 24" 25" 26" 27" 28" 29" 30" 500 500 500 500 500 500 500 500 500 500 500 500 500 500 500 500 500 400 400 400 400 400 500 500 400 400 400 400 400 400 350 400 400 400 400 350 350 350 350 350 300 300 300 300 300 300 300 300 300 300 300 300 250						

Spine Calculation based on Standard 50/60 Grain Insert

STANDARD VAP SPINE CHART											
Compound	Arrow Length										
Bow Rating 300-340 FPS	23"	24"	25"	26"	27"	28"	29"	30"	31"		
37-41					500	500	500	500	500		
42-46			500	500	500	500	450	450	450		
47-51		500	500	500	450	450	400	400	400		
52-56	500	500	450	450	450	400	400	350	350		
57-61	500	450	450	450	400	400	350	350	350		
62-66	450	450	400	400	350	350	350	300	300		
67-72	450	400	400	350	350	350	300	300	300		
73-78	400	400	350	350	300	300	300	300	250		
79-84	400	350	350	300	300	300	250	250	250		
85-90	350	350	300	300	250	250	250	250	250		
90-95	350	300	300	250	250	250	250	250			
95-100	300	300	250	250	250	250					
	Coins Collegation based on Chardend 25 Conin based										

Spine Calculation based on Standard 35 Grain Insert

If 75 grain insert is used, add 5 lbs draw weight. If 95 grain insert is used, add 10 lbs draw weight.

VICTORY ARCHERY SAFETY WARNING



ARCHERY SAFETY

Victory Archery is committed to safe archery. Archery/hunting requires a high level of skill and caution at all times to avoid personal injury or property damage. Victory Arrows should only be used by those trained in the proper use of bows and arrows or under the supervision of a qualified instructor.

Arrows should always be inspected before each use for signs of damage. Impact with hard objects, other arrows or being shot into a game animal can all cause damage. We recommend flexing each arrow and inspecting for any sign of cracks or splits before each use. Grasp the arrow between the point and nock, flex the arrow along its length so as to deflect it approximately 1 to 2" in an arc and listen for cracking. Never use an arrow with any sign of damage. A cracked or split arrow can suffer catastrophic failure upon release and cause severe injury to yourself or others in the area.

PRACTICE SAFE ARCHERY

After loading an arrow into a bow, never point at any person or property. An arrow can be accidentally discharged and cause

severe injury and property damage. Never shoot an arrow without having full visual contact with the target and knowing what is behind the target. Always inspect your bow, arrows and components prior to each use.

BOWHUNTING PRECAUTIONS

When hunting, the possibility of arrow damage increases significantly. This is due to the high likelihood of the arrow impacting various things (roots, trees, fences, posts, rocks, hard ground, bone, etc), possible misuse (improper maintenance, abuse, or care), impact with other arrows, or the angle in which it impacts/passes through an animal. Damage to the arrow can result in sharp and/or splintered carbon fragments which are harmful to humans, especially if ingested. If there is ANY suspected carbon arrow damage please utilize the guidelines listed below.

- Thoroughly inspect the entrance wound, exit wound, and surrounding area prior to removing the carbon arrow in order to determine whether or not there are splinters/ fragments imbedded in the game animal.
- 2) Use extreme caution when removing the broken segments of the carbon arrow shaft.
- While field dressing game animals, use care to avoid splinters/fragments of carbon fiber.
- 4) Carefully remove and dispose of any flesh that has the presence or suspected presence of carbon fiber splinters or fragments.

To err on the side of caution is always the best course of action. Victory Archery is committed to safe archery. Use good judgment in determining whether or not something is unsafe, incorrect, or there is a possibility of harm.

ARROW SAFETY WARNING

Victory Archery is committed to safe archery. Archery/hunting requires a high level of skill and caution at all times to avoid personal injury, death, or property damage. Victory products should only be used by those trained in the proper use of bows and arrows or under the direct supervision of a qualified instructor. After loading an arrow into a bow, never point at any person or property. An arrow can be accidentally discharged and cause severe injury, death, or property damage. Never shoot an arrow without having full visual contact with the target and knowing what is behind the target. Always inspect your bow, arrows, and components prior to each use. Careless handling of arrows or components can result in severe injury. If an arrow has been damaged, or appears to be damaged, dispose of it immediately.

NEVER ATTEMPT TO SHOOT A DAMAGED ARROW. INSPECT ARROWS FOR DAMAGE PRIOR TO EVERY SHOT

Impact with hard objects, other arrows, or being shot into a game animal can all cause damage. No list is all inclusive; there are many other conditions and situations that may cause damage, so it is crucial to your safety and the safety of those around you that all arrows and components (new or used) are inspected for possible damage. We recommend flexing each arrow and inspecting for any sign of cracks or splits before each use. Grasp the arrow between point and nock. Flex the arrow, away from you or others, along its length so as to deflect it approximately 1 to 2 inches in an arc and listen for cracking. Before shooting, run your fingertip along the entire arrow shaft length, feeling and looking for nicks, cracks, splits, dents, or other marks that could indicate any possible shaft damage. Never use an arrow with any sign of damage. A cracked or split arrow can suffer catastrophic failure upon release and cause severe injury to yourself and others in the area. Before each shot, ensure that the nock is fully seated against the string and that the nock fits tightly into the shaft. Adherence to these recommended guidelines will reduce the possibility of injury and promote a safe and fun archery experience.




CROSSBOW BOLT SAFETY WARNING

Victory Archery is committed to safe shooting practices. Crossbow shooting & hunting requires a high level of skill and caution at all times to avoid personal injury, death, or property damage. Victory products should only be used by those trained in the proper use of crossbows and bolts or under the direct supervision of a qualified instructor. After loading a boll into a crossbow, never point at any person or property. Bolts can be accidentally discharged and cause severe injury, death, or property damage. Never shoot a bolt without having full visual contact with the target and knowing what is behind the target. Always inspect your crossbow, bolts, and components prior to each use. Careless handling of bolts or components can result in severe injury. If a bolt has been damaged, or appears to be damaged, dispose of it immediately.

NEVER ATTEMPT TO SHOOT A DAMAGED BOLT. INSPECT BOLTS FOR DAMAGE PRIOR TO EVERY SHOT

Impact with hard objects, other bolts, or being shot into a game animal, can all cause damage. We recommend flexing each bolt and inspecting for any sign of cracks or splits before each use. Grasp the bolts firmly with both hands between the point and nock. Twist, flex and squeeze the shaft while listening for cracking. Never use bolts with any sign of damage. A cracked or split bolt can suffer catastrophic failure upon release and cause severe injury to yourself or others in the area.



ADDITIONAL SAFETY INFORMATION CAN BE FOUND AT WWW.VICTORYARCHERY.COM/SAFETY

WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

